Reference Number: 150925-BH1 Prepared: 2012年6月10日 Revised: 2018年3月30日

Product name:

H1 Bell Hammer 420 ml Mini Spray

1. Chemical substances and company information

Product name:	H1 Bell Hammer 420 ml Mini Spray		
Company name:	Suzuki Kikoh Co., Ltd.		
Address:	316-3 Matsuhidai, Matsudo, Chiba Prefecture 270-2214		
Department in charge:			
Emergency telephone No.	Telephone No.:	047-385-5311	FAX No.: 047-385-5313

2. Hazards identification

GHS classification of products, label element GHS Classification	S
Physio-chemical hazard	Aerosol: Category 1
Health Hazards	Specific target organ toxicity (single exposure): Category 2 Specific target organ toxicity (single exposure): Category 3 (Anesthetic acti Specific target organ toxicity (single exposure): Category 1
GHS Label Elements	
Signal word	Hazard
Hazard information	Extremely highly combustible or flammable aerosol. High-pressure container; may explode if heated. May cause organ damage. May cause drowsiness or dizziness. Prolonged or repeated exposure may cause organ damage.
Physical and chemical hazards	Contains high pressure flammable gas. May explode upon heating or impact. Contains flammable gas. Retained gas may explode. May ignite or burn when exposed to high temperatures.

3. Composition and information on ingredients

Classification of chemical substance or mixture
Composition and content

Ingredient name / Chemical name	Content (%)	CAS No.	nical Substance Control
Isobutane	10 to 20	75-28-5	(2)-4
n-butane	20 to 30	106-97-8	(2)-4
Propane	20 to 30	74-98-6	(2)-3

Note: These values are not specification values.

Reference Number: 150925-BH1 Prepared: 2012年6月10日 Revised: 2018年3月30日

Product name:

Refer to "15. Applicable laws" for ingredients applicable to Industrial Safety and Health Law and Law concerning Pollutant Release and Transfer Register (PRTR).

4. First aid measures

If inhaled:	Move to an area of fresh air and keep at rest in a position comfortable for breathing. Call a doctor if you feel unwell.
If on skin:	Immediately wipe off with a clean dry cloth. Do not use solvent or thinner. Wash with plenty of water and soap. If there is a change in appearance, if there is stimulation or pain or if you feel sick, consult a physician.
If in eyes:	Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Ensure that water reaches all areas of the eyes. If eye irritation persists, get medical advice/attention.
If swallowed:	Do not swallow vomit. Do not induce vomiting unless directed by a doctor. Rest and consult a physician immediately.
Protection of first-aiders:	Anyone helping the injured person should wear protective equipment such as rubber gloves and sealed goggles.

5. Firefighting measures

Extinguishing media	Appropriate extinguishing media. In case of fire, use foam, powder or carbon dioxide.
commendations on fire extinguish	Specific fire fighting methods: Spray water on sealed containers that have been exposed to high temperatures to cool. Conduct fire fighting activities from a windward location. Immediately remove flammable materials from the vicinity. In the case of aerosol products, conduct firefighting activities at a safe distance since aerosols may explode at high temperatures.
Protection for fire fighters	Wear appropriate protective equipment (such as heat-resistant clothing).

Reference Number: 150925-BH1 Prepared: 2012年6月10日 Revised: 2018年3月30日

Product name:

H1 Bell Hammer 420 ml Mini Spray

6. Accidental release measures

Personal precautions Protective equipment and emergency measures	Wear suitable protective equipment (gloves, protective mask, apron, goggles, etc.) when working Prevent secondary disasters by prohibiting entry into the surrounding area and keeping unauthorized persons at a distance.
Environmental precautions	Precautions should be taken to prevent an impact on the environment due to the release of spilled substances into rivers etc.
Methods and materials for containment and clean up	Recover spilled substance into a sealable container and transfer to a safe location. Dispose of debris and waste etc. in accordance with relevant laws and regulations.
Measures to prevent secondary	Install appropriate fire extinguishers in preparation for fires. Immediately remove any ignition sources, high temperature bodies or nearby

7. Precautions for handling and storage

Handling

Technical	Prevention of exposure of handler Avoid inhalation of dust, smoke, gas, mist, vapor or spray.	
	(Prevention of fire/explosion) Avoid ignition sources such as heat, sparks, open flames or high temperatures. No smoking. Do not spray on open flames or other ignition sources.	
Precautions for safe handling	Use only outdoors or in well-ventilated areas. Wear protective gloves, protective clothing, protective goggles and face shield. Do not puncture or burn, even after use.	
Incompatibilities Safe storage conditions	Appropriate storage conditions Store in a well-ventilated area. Keep container tightly closed. Store locked up.	
	Storage conditions to avoid Shield from sunlight. Do not store at temperatures of $\ge 40^{\circ}$ C.	

Reference Number: 150925-BH1 Prepared: 2012年6月10日 Revised: 2018年3月30日

Product name:

H1 Bell Hammer 420 ml Mini Spray

8. Exposure prevention and protection measures

Permissible

Name of component	Permissible Concentration		
	Japan Society for Occupational Health	ACGIH	
n-butane	500ppm (1998)	STEL: 1,000ppm (central nervous system impairment) (2012)	
Propane	Not established	Asphyxiation	
Isobutane	500ppm (1988)	STEL: 1,000ppm (central nervous system impairment) (2012)	

Exposure

1	Equipment measures	Handle in a location with adequate ventilation. Provide appropriate exhaust/ventilation equipment.
Protective		
	Respiratory	Wear respiratory protection.
	Hand protection	Wear protective gloves.
	Eye protection	Wear protective glasses and face protection.
	Skin and body protection	Wear protective clothing.
	Hygiene measures	Wash contaminated areas thoroughly after handling.
		Do not eat, drink or smoke while using this product.
		Do not eat, arms or smoke while using this product.

9. Physical and chemical properties

Information on basic physical and chemical properties Physical State

Shape	Liquid
Color	White
Odor	Characteristic odor

Specific temperature/temperature range at which the physical state changes

Initial boiling point/boiling point	(Propane) -42°C
Flash point	(Propane) -104°C
Spontaneous	365℃
ignition	303 C
Explosion	Ignition or explosion range
characteristics	
Lower limit	1.8vol%
Upper limit	9.5vol%
Specific	0.64±0.02g/cm3
gravity/density	0.0+±0.02g/cm3

Reference Number: 150925-BH1 Prepared: 2012年6月10日 Revised: 2018年3月30日

Product name: H1 Bell Hammer 420 ml Mini Spray

10. Stability and reactivity

Chemical stability:	Aerosol can products may explode at temperatures of \geq 40 °C.
Possibility of hazardous	May react with oxidizing substances etc. if they come into contact.
Conditions to avoid:	Avoid heating, sparks, open flames and other ignition sources.
Incompatible hazardous	Oxidizing substances.
Hazardous decomposition	Harmful gases such as carbon monoxide, nitrogen oxide and other low molecular weight monomers are generated upon combustion.

11. Toxicological information

Information on toxicological effects		
Acute toxicity	Isobutan	ne gas : mouse LC50=11000 ppm/4hr (ACGIH, 2004).
Immediate effects due to short-term exposure	/delayed or c	chronic effects due to long-term exposure
Specific target organ toxicity		
Specific target organ toxicity,	single	[Category
		Isobutane Heart
		[(Category 3 (Anesthetic action)]
		(n-butane) Anesthetic
		action
		(Propane) Anesthetic
		action
		(Isobutane Anesthetic
) action

12. Ecological information

Water

11- 11:4		
solubilitv	(n-butane)	0.0061 g/100 ml (20 C) (ICSC, 2003).
	(Propane)	0.007 g/100 ml (20 C) (ICSC, 2003).
	(Isobutane)	Not soluble (ICSC, 1998).
Bioaccumulative potential (Propane)		log Pow=2.36 (ICSC, 2003).
	(Isobutane)	log Pow=2.8 (ICSC, 1998).

Reference Number: 150925-BH1 Prepared: 2012年6月10日 Revised: 2018年3月30日

Product name: H1 Bell Hammer 420 ml Mini Spray

(n-butane) log Pow=2.89 (ICSC, 2003).

Other May impact the environment so handle spillages and disposal with care.

In particular, do not allow the product or washing water to flow directly onto the ground or

13. Disposal considerations

Waste treatment method

Avoid release to the environment.

Dispose of contents and containers according to local and national regulations.

Do not incinerate aerosol products.

Use the entire content of aerosol products. Throw out once the gas has been completely expelled. Do this outdoors and away from fire by pushing the button until the jet sound disappears.

Never dispose of products that still contain product. Take precautions to avoid inhaling fire or mist when expelling gas.

Contaminated containers and packaging

Do not puncture or burn, even after use.

14. Transport information

UN number, UN classification No.	1950	
Product name (UN shipping name)	Aerosol, flammable	
UN classification (Hazard class in transportation)	2.1	
Guideline number	126	

15. Applicable laws

Safety, health and environmental regulations, laws and ordinances specific to this product. Does not fall under the Poisonous and Deleterious Substances Control Law.

Industrial Safety and Health Law Labeling of dangerous/harmful substances (Article 57-2, Appended table 9 of Article 18 -2 of the order). n-butane; Isobutane

Appended Table 1 Hazardous materials (Relating to Articles 1, 6 and 1: Hazardous materials/Flammable gases (Appended Table 1, Item 5 of the order).

Name notification Hazardous/harmful materials (Article 57-2, Appended table 9 of Article 18-2 of the order) n-butane; Isobutane

Reference Number: 150925-BH1 Prepared: 2012年6月10日 Revised: 2018年3月30日

Product name:

H1 Bell Hammer 420 ml Mini Spray

Does not fall under the Law concerning Pollutant Release and Transfer Register (PRTR).

Fire Service Act Category 4 Inflammable liquids Class 4 petroleums Danger level III.

High Pressure Gas Safety Law Since this aerosol product has a capacity of ≤ 1 liter and a pressure of ≤ 0.8 MPa at 35°C, the High Pressure Gas Safety Law does not apply.

Ship Safety Law Gas Flammable gas Classification 2 Category 2.1

Civil Aeronautics Law High pressure gas flammable gas Classification 2 Category 2.1

16. Other information

References	 Globally Harmonized System of Classification and Labelling of Chemicals, (5th ed., 2013), Recommendations on the TRANSPORT OF DANGEROUS GOODS 19th edit., 2015 UN. Classification, labelling and packaging of substances and mixtures (table3-1 ECNO6182012). 2012 EMERGENCY RESPONSE GUIDEBOOK(US DOT). 2018 TLVs and BEIs. (ACGIH). <u>http://monographs.iarc.fr/ENG/Classification/index.php</u> JIS Z 7253 (2012) JIS Z 7252 (2014) 2017 Recommendations on permissible concentrations (Japan Society for Occupational Supplier's data/information.
Limitation of liability	These contents were created based on materials and information data available at the time of preparation and may be revised by new findings. Precautions are subject to normal handling so appropriate safety measures must be implemented in the case of special handling.